

Sub-Surface Stormwater Storage System

Product:

ST-36



Technical Data

Nominal Specifications		
Size	36"x18"x36" (914x457x914 mm)	
Void Space	97.0%	
Module Storage	13.10 cf (0.37 m ³)	
Installed Storage	15.80 cf (0.45 m ³)	
Weight	33.10 lbs. (15 kg)	

Notes:

 Installed storage assumes 6" of stone below, 12" stone above and 40% porosity for the stone plus the module volume.

Shipping Information

Description	Packaged Quantity	Packaged Weight lbs. (kg)
Top/Bottom Platens	84 / skid	568 (258)
	126 / skid	853 (387)
Side Panels (3ft length)	90 / skid	367 (166)
Columns	336 / skid	902 (409)

Manufacturer:




Distributed by:


R. H. Moore & Associates, Inc. (O): 813-988-0200 (F): 813-985-4533 info@rhmooreassociates.com www.rhmooreassociates.com


© 2012 Brentwood Industries StormTank® is a registered trademark of Brentwood Industries

StormTank™ Stormwater Storage System is a high-void, high strength, affordable alternative to crushed stone, concrete structures, or pipe chambers. Use of StormTank™ reclaims valuable surface space for better surface usage such as recreational areas, parking lots or buildings.

StormTank™ module design provides the maximum storage volume while minimizing the installation footprint to reduce construction costs. The open module design, with no partitions or walls between modules, allows for easy inspection and cleaning.







Disclaimer: Brentwood Industries (Brentwood) assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. Brentwood Industries disclaims any and all other warranties, expressed or implied with respect to any service or deliverable other than those expressly provided in this (section, paragraph, quotation, proposal, etc.) including without limitation any implied warranty of merchantability or fitness for a particular purpose This document should not be construed as engineering advice.